


Q-SYS MPA-Q SERIES

Network amplifiers

KEY FEATURES

- **MPA-Q 4×250:** Four (4) output channels at 250 W per channel
- **MPA-Q 4×500:** Four (4) output channels at 500 W per channel
- **MPA-Q 8×125:** Eight (8) output channels at 125 W per channel
- **MPA-Q 8×250:** Eight (8) output channels at 250 W per channel
- Lo-Z, Hi-Z, 70 V and 100 V direct drive available on all channels (no bridging or manual switches required)
- Analog, line-level audio inputs per output channel, fully routable into Q-SYS or direct out
- Two (2) gigabit Ethernet ports for redundant networked audio
- Quiet fan-cooled design allows for co-location with loudspeakers
- Quick audio restore after a power outage if PoE connection is available
- Standalone mode automatically switches to available analog inputs if network connectivity drops
- Analog Mode bypasses networked audio and creates a fully analog amplifier. Front panel display allows basic channel configuration in this mode.
- Four (4) GPI inputs and two (2) NO/NC output relays
- Full-rack width, 2RU form factor and included hardware for rack- or surface-mounting



RIGHTSIZED FOR MEDIUM-TO-LARGE SPACES

MPA-Q Series introduces a new mid-power tier to the Q-SYS network amplifier portfolio and is ideal for spaces where high-output amplifiers exceed operational needs, like hospitality and retail facilities, entertainment spaces and larger corporate and government environments.

ADAPT TO KEEP AUDIO FLOWING

Ensure your audio system stays running with minimal interruptions. If network connectivity drops, MPA-Q Series amplifiers offer the ability to automatically switch the source to available analog inputs to maintain sound continuity. In the event of a power outage, network audio can be restored within seconds if a PoE connection is available.

VENUE-WIDE AUDIO WITH Q-SYS

MPA-Q Series network amplifiers extend a seamless Q-SYS experience to even more spaces, delivering native audio routing and control in both distributed and performance audio applications throughout your venue.

INTEGRATED AUDIO, VIDEO AND CONTROL

MPA-Q Series network amplifiers are driven by the Q-SYS Full Stack AV Platform, which unifies data, devices and a cloud-first open architecture to deliver a fully integrated audio, video and control solution that offers simpler integration and software-based scalability.

	MPA-Q 4x250	MPA-Q 4x500	MPA-Q 8x125	MPA-Q 8x250					
AUDIO									
AMPLIFIER OUTPUT									
Freq response @ 20 Hz - 20 kHz, 8Ω		+0.2 dB / -0.7 dB							
Output THD+N @1kHz		0.01%-0.03% typical; 1% max							
SNR @ 20Hz-20kHz, 8Ω, A-weighted		>112 dB							
Gain @ +4 dBu input	31 dB	34 dB	28 dB	31 dB					
Damping factor		>160							
ANALOG INPUTS (LINE LEVEL ONLY)									
Input dynamic range		>108 dB							
Input impedance @ 1kHz		>1k balanced and >5.5k unbalanced							
Sample rate		48 kHz							
OUTPUT POWER									
	MPA-Q 4x250	MPA-Q 4x500	MPA-Q 8x125	MPA-Q 8x250					
Loads	Maximum ¹	Continuous ²	Maximum	Continuous					
All channels driven A, B, C, D	100 V	250 W	150 W	500 W	300 W	125 W	75 W	250 W	150 W
	70 V	250 W	150 W	500 W	300 W	125 W	75 W	250 W	150 W
	8Ω	250 W	150 W	500 W	300 W	125 W	75 W	250 W	150 W
	4Ω	250 W	150 W	500 W	300 W	125 W	75 W	250 W	150 W
	2Ω	250 W	150 W	500 W	300 W	125 W	75 W	250 W	150 W
Single channel driven A or B or C or D	100 V	TBD	TBD	TBD	TBD	TBD	TBD	TBD	TBD
	70 V	TBD	TBD	TBD	TBD	TBD	TBD	TBD	TBD
	8Ω	TBD	TBD	TBD	TBD	TBD	TBD	TBD	TBD
	4Ω	TBD	TBD	TBD	TBD	TBD	TBD	TBD	TBD
	2Ω	TBD	TBD	TBD	TBD	TBD	TBD	TBD	TBD
2 channels bridged A+B or C+D	100 V	500 W	300 W	1000 W	600 W	250 W	150 W	500 W	300 W
	70 V	500 W	300 W	1000 W	600 W	250 W	150 W	500 W	300 W
	8Ω	500 W	300 W	1000 W	600 W	250 W	150 W	500 W	300 W
	4Ω	500 W	300 W	1000 W	600 W	250 W	150 W	500 W	300 W
	2Ω	Not supported		Not supported		Not supported		Not supported	

1. **Max Power:** 20 ms, 1kHz sine wave burst; this data is most useful for asymmetrical loading of amplifier channel and maximizing power utilization of the amplifier.

2. **Continuous power:** 20 Hz - 20 kHz bandwidth, all channels driven with same load; this data is most useful for estimating longer-term power output across all amplifier channels.


ENVIRONMENTAL

Operating temp	32° TO 104° F (0° - 40° C)		
Storage temp	-4° TO 158° F (-20° TO +70° C)		
Humidity range	5% - 85% RH		
Fan noise (idle & max)	34dBA typical, 50dBA max		
Cooling	Forced air cooling, thermally regulated fan speed, front-to-rear airflow		


PHYSICAL

Audio I/O connections	Output: 4x channels (Euro 7.62 mm) Input: 4x channels (Euro 3.5 mm)	Output: 4x channels (Euro 7.62 mm) Input: 4x channels (Euro 3.5 mm)	Output: 8x channels (Euro 7.62 mm) Input: 8x channels (Euro 3.5 mm)	Output: 8x channels (Euro 7.62 mm) Input: 8x channels (Euro 3.5 mm)
Networking	2x 1 Gbps Ethernet ports LAN A optionally accepts PoE (802.3af Type 1) for quick time-to-audio following a power interruption			
GPI	0-3.3V DC Closure			
Mounting options	Front rack ears come installed for rack mount installation (rack ears can also be used for chassis-supported surface-mounting)			
Controls and indicators (front)	Buttons: Page, Edit, ID, Mute All Pin: Reset Control Knob OLED Screen Clip, Limit, Bridge LED Indicators			
Controls and indicators (back)	Q-SYS / Analog Mode switch			
AC power input	100-240 V, 50/60 Hz, 2.8-1.8 A	100-240 V, 50/60 Hz, 4.6-2.5 A	100-240 V, 50/60 Hz, 3.2-2.0 A	100-240 V, 50/60Hz, 5.2-2.8 A
Product dimensions (L x W x H)	15.0 x 19.0 x 3.5 in (381 x 483 x 89 mm)			
Package dimensions (L x W x H)	20.4 x 23.3 x 7.7 in (519 x 592 x 192 mm)			
Product weight	19.4 lbs (9.0 kg)	20.7 lbs (9.4 kg)	22.5 lbs (10.2 kg)	22.9 lbs (10.4 kg)
Package weight	25 lbs (11.4 kg)	26 lbs (11.8 kg)	28 lbs (12.7 kg)	28 lbs (12.7 kg)
Agency approvals	TUV, CE, ROHS/WEEE compliant, FCC Class A (conducted and radiated emissions)			
Included accessories	1x AC mains power cord (country specific) Removable rack ears for rack- or surface-mounting 4-position 7.62mm pitch Euroblock connectors (Qty 4) 3-position 3.5mm pitch Euroblock connectors (Qty 8) 12-position (2-row) 3.5mm pitch Euroblock connector (Qty 1)			
	1x AC mains power cord (country specific) Removable rack ears for rack- or surface-mounting 4-position 7.62mm pitch Euroblock connectors (Qty 8) 3-position 3.5mm pitch Euroblock connectors (Qty 16) 12-position (2-row) 3.5mm pitch Euroblock connector (Qty 1)			


MPA-Q 4x250



MPA-Q 4x500



MPA-Q 8x125



MPA-Q 8x250

